

Copyright © 2016 SKOPE industries Limited				
GENERAL SPECIFICATIONS				
Temperature range	1°C to 4°C (adjustable up to 15°C)			
Climate class	5 (Tested at 43°C)			
Doors	Lockable, self-closing, double glazed, single Low-E, argon filled, toughened safety glass swing doors (hing LH, RH, RH)			
Internal Volume	1497 litres			
Shelves	15 adjustable height wire shelves: 500 wide × 470mm deep (5 each side), 570 wide x 470 deep (5 middle)			
Power supply	220-240 Volts a.c. 50 Hz, single phase supply. Supplied with 10 Amp 3-Pin plug			
Current draw	4.8 Amps (includes unit 4.0 Amps)			
Refrigeration system	Removable ActiveCore top mount refrigeration unit (UTHCCI-0004)			
Refrigerant	R134a / 475g			
Nominal capacity	1000 Watts			
Controller	Carel S4 electronic controller			
Drainage	No plumbing required			
Weight	320 kg			

INDIVIDUAL SPECIFICATIONS

Model	SKT1500-A	SKT1500-AC	SKT1500-ACX	
Part number	MT15GY	MT15BY	MT15BX	
Sign	Sign replacement panel	400mm high illuminated sign		
Sign lighting	n.a.	1 × 22W T8 LED tube (Ø26mm × 1500mm)		
Interior side lights	3 × 20W (1400mm) LED module s	n.a.		
Interior shelf lights	n.a.	n.a.	15 x 7W LED module strip shelf lights	
SKOPE Industries Limited reserve the right to alter specifications without notice.			PSS0431 Rev. 2.2 Mar. 2018	

SKOPE Industries Limited reserve the right to alter specifications without notice.



Practical Products Pty Ltd, 51 Paramount DSrive Wangara WA 6065 Ph: 08 9302 1299, Email: sales@practicalproducts.com.au SKOPE INDUSTRIES LIMITED Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673

Email: skope@skope.co.nz, Website: www.skope.com