

BROMIC[®] Ice Cream/ Gelato Display

REFRIGERATION



Gelato
Angle Top Flat Glass - 7 basket
GD0007S/Slim



Gelato
Angle Top Flat Glass - 7 basket
GD0007S



Gelato
Angle Top Flat Glass - 7 tubs
FENICE7



Sliding lid



Interior casing



Curved glass cover



5 litre storage tubs

These Ice Cream displays offer an attractive solution for display of ice creams. The units can be decalced (additional charges apply POA)

- Curved display canopy for safety, hygiene and visual effect
- Easy clean condensor design for better protection
-less condensation, less rust, less humidity - even in tropical climates
- Digital Temperature display
- Castors for easy positioning
- Corrosion resistant construction and equipped with defrost water drain

	GD0007S/Slim	GD0007S	FENICE7
Bromic Part Number	3735311	3735262	3736205
No. of Baskets	7 baskets	7 baskets	7 tubs
Additional Storage (No. of 5 Litre tubs)	Yes	Yes	Yes - 12 x 5L tubs
Dimensions - with castors (mm)	1327w x 516d x 1229h	1298w x 615d x 1296h	1314w X 702d X 1165h
Internal dimensions (mm)	1210w x 395d x 705/630h	1180w x 495d x 708/610h	1190w x 505d x 755h
Temperature range (°C)	-12°C to -22°C	-12°C to -22°C	-18°C to -25 C
Max. ambient temp. (°C/RH%)	35°C / 70%	35°C / 70%	+25C /60 %
Air Flow	Static	Static	Fan assisted
Type of control	Analogue	Analogue	Electronic
Temperature display	Digital	Digital	Digital
Product and interior lighting	n/a	n/a	LED
Front glass	Curved Tempered	Curved Tempered	Curved Tempered
Defrosting	Manual	Manual	Automatic
Refrigeration Power (watts)	300W	300W	1100W
Current (Amps)	2.3A	2.3A	6.7A
Gross weight (kg)	82kg	81kg	148Kg
Refrigerant	R404a	R404a	R404a
Colour	White	White	White
Power Usage (at 30°C/60%RH)	4.9Kw/24hr	4.9Kw/24hr	15.1 KW/24hr
Plug supplied	Yes 10A	Yes 10A	Yes 10A
	 1327mm x 516mm	 1298mm x 615mm	 1314mm x 702mm
	 1229mm Side View	 1296mm Side View	 1165mm Side View

WARRANTY 1 yr PARTS
1 yr LABOUR