700XP 6-Hot Plates Electric Boiling Top Range

	Electrol	υx
--	----------	----

Modular Cooking Range Line 700XP 6-Hot Plates Electric Boiling Top Range

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



Modular Cooking Range Line

700XP 6-Hot Plates Electric Boiling Top Range

371019 (E7ECEL6R00)

6-hot plate (2,6 kW each) electric boiling top

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. Six 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The six 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPX 4 water protection.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories

•	Junction sealing kit	PNC	206086
•	Kit 4 wheels - 2 swivelling with brake - it is mandatory to install base support and wheels	PNC	206135
•	Support for bridge type installation, 1200mm	PNC	206139
•	Support for bridge type installation, 1400mm	PNC	206140
•	Support for bridge type installation, 1600mm	PNC	206141
•	Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC	206178
•	Water column with swivel arm (water column extension not included)	PNC	206289
•	Water column extension for 700 line	PNC	206291
•	Chimney upstand, 200mm	PNC	206302
•	Chimney upstand, 800mm	PNC	206304
•	Right and left side handrails	PNC	206307
•	Base support for feet or wheels - 800mm (700/900)	PNC	206367
•	Base support for feet or wheels - 1200mm (700/900)	PNC	206368
•	Rear paneling - 1200mm (700/900)	PNC	206376
•	Chimney grid net, 400mm (700XP/900)	PNC □	206400
•	Frontal handrail, 1200mm	PNC □	216049
•	Frontal handrail, 1600mm	PNC	216050
•	Large handrail - portioning shelf, 800mm	PNC	216186
•	2 side covering panels for top appliances	PNC	216277

APPROVAL:



Modular Cooking Range Line 700XP 6-Hot Plates Electric Boiling Top Range

Front 47 1/4 " 1200 mm 13 1/16 " 332 mm ΕQ ₩₩ ΕI 3 15/16 " 100 mm 2 1/16 52 mm 0 7/16 " 46 3/8 " 0 7/16 " 11 mm 1178 mm 11 mm Top 3 15/16 " 100 mm 3 15/16 100 mm EI = Electrical connection **Equipotential screw** Side 15/16 74 mm 7/16 28 3/4 " 28 730 mm 9 7/8 " 250 mm 0 15/16 " 24 mm 4 1/16 " ΕQ 103 mm 1 9/16 " ΕI 40 mm 17 11/16 " 4 5/8 " 5 7/8 " 148 mm 450 mm 117 mm

Electric

Supply voltage:

371019 (E7ECEL6R00) 400 V/3 ph/50/60 Hz

Total Watts: 15.6 kW

Key Information:

Front Plates Power: 2.6 - 2.6 kW
Back Plates Power: 2.6 - 2.6 kW
Front Plates dimensions: Ø 230 Ø 230
Back Plates dimensions: Ø 230 Ø 230
Net weight: 60 kg

Shipping weight: 70 kg
Shipping height: 540 mm
Shipping width: 830 mm
Shipping depth: 1300 mm
Shipping volume: 0.58 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

