

Blue Seal Electric Combi Steamer

COMPACT SAPIENS RELOADED EC611RSDW 6 x 1/1 GN



- Compact 510mm wide
- Manual controls
- Electric direct steam version
- LED HVS (High Visibility System) alphanumeric display for temperature, Autoclimate, time and core temperature
- 2.4" LCD-TFT colour display with rapid selection scroller knob for program and setting selection
- Two speed fan
- Over 95 preset recipe programs
- 99 free programs with up to 9 cycles in automatic sequence
- Electronic thermostat 30° – 300°C
- Manual pre-heating
- Auto-reversing fan rotation
- Autoclimate with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Multipoint core temperature probe
- Automatic LCS (Liquid Clean System) with built-in tank and automatic dispensing
- ECOVAPOR – automatic control of the steam saturation in the cooking chamber
- ECOSPEED – oven optimizes and controls the delivery of energy to maintain correct cooking temperature
- Externally connected hand shower
- USB connection

GENERAL FEATURES

- Direct Steam injection system
- Perfectly smooth, water tight chamber
- Double tempered glass door with air chamber and interior heat-reflecting glass reduces heat radiation towards operator
- Hinged inner glass for easy cleaning
- Adjustable door hinge for optimal seal
- Fan motor thermic protection
- Low water alarm
- Component cooling system with overheat display control
- Self-diagnosis and fault display
- Oven light
- IPX4 spray-proof and hose proof

OPTIONAL FEATURES

- Right hinged door
- Configuration for connection to extraction hood



Sapiens®
reloaded

Blue Seal Electric Combi Steamer

COMPACT SAPIENS RELOADED EC611RSDW 6 x 1/1 GN

Dimensions

Width	510mm
Depth	800mm
Height	880mm
Weight	73kg

Packed dimensions

Width	570mm
Depth	930mm
Height	1020mm
Weight	82kg

Shelves

1/1 GN	6
Shelf Spacings	60mm

Installation requirements
(for precise installation instructions, please refer to the unit's installation manual).

Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

Supply line voltage

400-415V - 50Hz, 3P+N+E

Special voltage options available on request.

Power connection

Total (kW)	7.75
Convection power (kW)	7.5
Rated Current (A) (400V)	12

Installation clearances

- rear	50mm
- right	500mm*
- left	50mm

*Clearance required on fixed installations for service accessibility.


If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 500mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

Water connection requirements

- Cold water
- Flow pressure (200-500kPa)
- Soft water connection*
- Shut-off valve with return flow inhibitor and dirt filter
- Water supply x2 R $\frac{3}{4}$
- R40 waste water connection

(*Water softener may be required. Please refer to installation manual for water treatment values.)



WA DEALER
PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299
51 Paramount Dr Wangara WA 6065
sales@practicalproducts.com.au
www.practicalproducts.com.au