

Sapiens®  
reloaded

## Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC623RSDW 6 x 2/3 GN



- Compact 510mm wide
- Manual controls
- Electric direct steam version
- LED HVS (High Visibility System) alphanumeric display for temperature, Autoclimate, time and core temperature
- 2.4" LCD-TFT colour display with rapid selection scroller knob for program and setting selection
- Two speed fan
- Over 95 preset recipe programs
- 99 free programs with up to 9 cycles in automatic sequence
- Electronic thermostat 30° – 300°C
- Manual pre-heating
- Auto-reversing fan rotation
- Autoclimate with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Multipoint core temperature probe
- Automatic LCS (Liquid Clean System) with built-in tank and automatic dispensing
- ECOVAPOR – automatic control of the steam saturation in the cooking chamber
- ECOSPEED – oven optimizes and controls the delivery of energy to maintain correct cooking temperature
- Externally connected hand shower
- USB connection

### GENERAL FEATURES

- Direct Steam injection system
- Perfectly smooth, water tight chamber
- Double tempered glass door with air chamber and interior heat-reflecting glass reduces heat radiation towards operator
- Hinged inner glass for easy cleaning
- Adjustable door hinge for optimal seal
- Fan motor thermic protection
- Low water alarm
- Component cooling system with overheat display control
- Self-diagnosis and fault display
- Oven light
- IPX4 spray-proof and hose proof

### OPTIONAL FEATURES

- Right hinged door
- Configuration for connection to extraction hood



**Sapiens®**  
reloaded

# Blue Seal Electric Combi Steamer

## COMPACT SAPIENS RELOADED EC623RSDW 6 x 2/3 GN

### Dimensions

Width	510mm
Depth	625mm
Height	880mm
Weight	59kg

### Packed dimensions

Width	570mm
Depth	760mm
Height	1020mm
Weight	68kg

### Shelves

2/3 GN	6
Shelf Spacings	60mm

### Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

### Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

### Supply line voltage

400-415V - 50Hz, 3P+N+E

Special voltage options available on request.

### Power connection

Total (kW)	5.25
Convection power (kW)	5
Rated Current (A) (400V)	8

### Installation clearances

- rear	50mm
- right	500mm*
- left	50mm

\*Clearance required on fixed installations for service accessibility.


If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 500mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

### Water connection requirements

- Cold water
- Flow pressure (200-500kPa)
- Soft water connection\*
- Shut-off valve with return flow inhibitor and dirt filter
- Water supply x2 R $\frac{3}{4}$
- R40 waste water connection

(\*Water softener may be required. Please refer to installation manual for water treatment values.)



**WA DEALER**  
**PRACTICAL PRODUCTS PTY LTD**

PH: 08 9302 1299  
51 Paramount Dr Wangara WA 6065  
sales@practicalproducts.com.au  
www.practicalproducts.com.au