



## FED-X S/S Three Door Bench Freezer - XUB7F18S3V

### Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- 1 shelf per door, 1 GN1/1 pan compatible
- Self-closing doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls
- Rapid recovery rate
- Optional 2 and 3 drawer units available in lieu of doors
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Unit can be placed against the wall
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1234mm W x 580mm D x 564mm H

### Description

#### FED-X Stainless Steel Three Door Bench Freezer - XUB7F18S3V

This commercial freezer is perfect if you ' re running a busy business and looking for reliability and performance. Ideal choice for restaurants, cafe ' s, fast food operations, butcheries and convenience stores. With fan-forced cooling that ensures even distribution of the cool air there will be no warm spots and your food will be safe. This unit is designed for you to be able to maximize the internal space. You can place it under an existing counter or place it against the wall. Equipped with heavy-duty castors, ( brake type at the front) you can easily move the unit out for cleaning or maintenance.

Constructed with stainless steel interior and exterior, your unit is easy-to-clean and is made strong to withstand the rigors of a busy operation. All 3 doors are self-closing and fitted with heavy-duty magnetic seals to retain foods' optimal quality. You can set the temperature a single degree at a time with its user-friendly digital control.

This unit is GN compatible, comes with a single shelf but you can opt for additional slides so you pans just slide in and out.

We can provide Splashback tops as well as a 2 and 3 drawer option in lieu of a door which is available upon request.

This underbench fridge ' s build quality, specifications and functionality meet food, health, and safety standards.

\*Due to it ' s design, this unit can be placed against the wall.

\*Tropicalised for Australian conditions.

- Net Capacity: 417L
- Temperature range: -18 ~ -22 ° C & Ambient Temperature: 43 ° C & RH: 40%
- Cooling System: Fan forced cooling
- Compressor: Embraco/Secop
- Controller: Dixell
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1234mm W x 580mm D x 564mm H

## MAIN FEATURES

- Stainless steel interior and exterior with rounded corners for easy cleaning
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls
- Rapid recovery rate
- Optional 2 and 3 drawer units available in lieu of doors
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Unit can be placed against the wall

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice



**WA DEALER**  
**PRACTICAL PRODUCTS PTY LTD**

PH: 08 9302 1299  
51 Paramount Dr Wangara WA 6065  
[sales@practicalproducts.com.au](mailto:sales@practicalproducts.com.au)  
[www.practicalproducts.com.au](http://www.practicalproducts.com.au)

Your Shipping Specifications

Net Weight (Kg)	146
Width (mm)	1795
Depth (mm)	700
Height (mm)	850
Packing Width (mm)	1825
Packing Depth (mm)	730
Packing Height (mm)	910
Power	240V; 50V; 10A; 650W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice