



FED-X S/S Single Door Upright Freezer - XURF400SFV

Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Integrated door handle for easy cleaning
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 567mm D x 1394mm H

Description

FED-X S/S Single Door Upright Freezer - XURF400SFV

- Net Capacity: 429L
- Cooling System: Fan forced cooling
- Temperature range: -18~-22 ° C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Integrated door handle for easy cleaning
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 567mm D x 1394mm H



WA DEALER
PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299
51 Paramount Dr Wangara WA 6065
sales@practicalproducts.com.au
www.practicalproducts.com.au

Your Shipping Specifications

Net Weight (Kg)	111
Width (mm)	680
Depth (mm)	710+30
Height (mm)	2000
Packing Width (mm)	710
Packing Depth (mm)	740
Packing Height (mm)	2150
Power	240V; 10A; 450W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice