



ELEVATION SERIES CUBE ICE MAKER CIMO525



Model:

□ CIMO525



CIMO525 ON B42

Features and Benefits

- 22.25" (565 mm) wide space-saving design.
- Produces up to 240kg of ice per day.
- *Energy and Environment*
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
 - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - Built in Agion® ensures unbeatable antimicrobial protection.
 - Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling.
 - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

Ice Form

FULL CUBE DIMENSIONS	
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (mm)	10 x 22 x 22



CUBE

Bin Chart *Kits for Combining Wider Bins with Smaller Models*

ICE STORAGE BINS									
	Model No.	B25	ICB110SC	B40	B42	ICB180SC	B55	ICB230SC	CIB400
	Capacity	110 kg	110 kg	156 kg	160 kg	180 kg	232 kg	232 kg	400 kg
	Width	762 mm	560 mm	762 mm	559 mm	760 mm	762 mm	764 mm	1,220 mm
Kits									
	CIMO525	BT55	Kit Not Required	BT55	Kit Not Required	BT55		NA	

*See Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIMO525	CD20B	CD200B

Note: All modular cube CIM units can be installed with the O₃-Matic™ Ozone Delivery System.

Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts



ELEVATION SERIES CUBE ICE MAKER CIMO525




CIMO525 CUBE ICE MAKER


Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, $\frac{3}{8}$ " FPT.
- B. Ice maker water out, $\frac{3}{4}$ " FPT.
- C. Hole for electrical connections, $\frac{7}{8}$ ".
- D. Electrical connection junction box, $\frac{7}{8}$ ".



Dual Exhaust for Installation Flexibility



Operating Requirements

	MINIMUM	MAXIMUM
		50Hz
Ambient Temp. Range Air	10°C	43°C
Water Temp.	4.4°C	
Water Pressure	1.4 BAR	5.5 BAR

Dimensions

ALL MODELS	
W x D x H (mm)	565 x 616 x 540

Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage litres per 45 kg of Ice 32°C air/21°C water		kWH Used per 45 kg of ice @ 32°C air/ 21°C water	Watts Used Per Hr @ 32°C air/ 21°C water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Refrigeration Capacity per hour
		21°C air/ 10°C water (kg)	32°C air/ 21°C water (kg)	Potable	Condenser						
CIMO525A	Air	240	193	76	-	6.11	1091	220-240/50/1	11.2	16	1,832

* Daily ice production based on half cube configuration.

Notes:
Number of Wires: 3 (including ground)
Approx. Shipping Weight kg: CIMO525A 75
Refrigerant Type: R404A



WA DEALER
PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299
51 Paramount Dr Wangara WA 6065
sales@practicalproducts.com.au
www.practicalproducts.com.au

Rev: 01/18
Part: C006