

LKPv 6523

MediLine



LED



Gross/net capacity	617/430 litre
Ext. dimensions in mm (w/d/h)	700/830/2160
Int. dimensions in mm (w/d/h)	533/650/1500
Energy consumption in 365 days	571 kWh
Ambient temperature range	+10°C to +40°C ¹
Refrigerant	R 290
Connection Rating	2.0 A
Voltage	220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	0°C to +16°C
Housing material/colour	steel/white
Door material	Insulated glazed door
Liner Material	304-grade stainless steel
Type of Control	electronic controller
Temperature display	external digital
Interior light	LED
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Adjustable Shelving	4
Castors	castors with brake at the front, fixed castors at the rear
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	83-60 mm
Gross/net weight	163/136 kg
EAN-Nr.	9005382196779

WA DEALER
PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299
51 Paramount Dr Wangara WA 6065
sales@practicalproducts.com.au
www.practicalproducts.com.au



LIEBHERR

¹ Indicates the ambient temperature at which the device can be operated safely.