



EC Series Self Contained Gourmet Ice Machines – with Progressive Water Discharge – up to 140kg

ECS 226 AS OX Small gourmet cube 8g, Ø21mm x 25mm



Small gourmet cube 8g, 21mm dia x H 25mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 140kg daily production rate
- 70kg storage bin capacity
- Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- PWD-Progressive water discharge: pumps excess residual water up to a distance up to 15 meters
- XSafe Natural Sanitation System
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Horizontal ice evaporator spray-system technology
- Resistant stainless steel exterior
- Front access condenser air filter, removable and washable
- Easy access front ON-OFF switch

- Routine maintenance visible alarm light on front panel
- Ergonomically designed ice storage access with disappearing door and door closing movement dampening system
- Includes ice scoop, water and drain hose




























EC Series Self Contained Gourmet Ice Machines — with Progressive Water Discharge — up to 140kg

ECS 226 AS OX








UNIT OF MEASUREMENT: **mm**

- 1. 25/32" OD OVERFLOW DRAIN
- 2. 3/4" WATER INLET
- 3. 3/4" WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET



Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
145	140	110

Dimensions

Width: 1078mm Depth: 719mm

Height: 1082mm (including legs)

Nett weight: 96kg Packed weight: 112kg

Water consumption

Air cooled version: 16.7 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 1150W,

10A cordset supplied

No. Circuit wire: 3 Compressor: 2650W Energy consumption: 24.7kW/hr

Refrigerant type

R404a

Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R ³/₄"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø³/₄"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

© Copyright Moffat Ltd

