

BACK BAR



_ FEATURES / BENEFITS **=**_

HOT GAS CONDENSATE SYTEM

Through SKIPIO's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■EFFICIENT REFRIGERATION SYSTEM

SKIPIO's refrigerators are designed with oversized and balanced refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■FORCED AIR COOLING SYSTEM

Fast cooling and balanced temperature throughout the cabinet.

*LED INTERIOR LIGHTING FOR ALL MODELS

Bright LED interior lighting is specifically designed for perfect visibility throughout the interior.

MAGNETIC DOOR GASKETS

Magnetic door gastkers are of one piece construction, removable without tools for ease of cleaning and replacement.

HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure is foamed-in-place using high density, CFC CFC free polyurethane insulation.

ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE)

COATED WIRE SHELVES

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

FRONT BREATHING SYSTEM

Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.



| Model | Doors | Capacity (Liters) | Shelves | Compressor (HP) | Amps (A) | Weight (Kg) | L X D X H (mm) |
|---------|-------|----------------------|---------|--------------------|----------|-------------|---------------------------|
| SB13-3G | 3 | 261 | 6 | 1/3 | 3.5 | 95 | 1352x550 ₃ 900 |

BACK BAR



Model: SB13-3G(800MM)

| SPEC SHEET | SB13-3G | | |
|---------------------------------|---|--|--|
| Classification | Refrigerator | | |
| Cabinet Dimension (WxDxH mm) | 1352x550) 900mm | | |
| Capacity (Liters) | 261 | | |
| Inner Temperature | 1°C~8°C | | |
| Doors | 3 | | |
| Number of Shelves | 6 | | |
| Refrigent | R-134a | | |
| Compressor (Hp) | 1/3 | | |
| Cooling Type | Fan cooling type | | |
| Insulation Type | Polyurethane / Cyclopentane + CFC Free | | |
| Temperature Control Type | Digital | | |
| Amps (A) | 3.5 | | |
| Voltage (V/Hz/Ph) | 240V 50Hz 1Ph | | |
| Power (W) | 330 | | |
| Weight (Kg) | 95 | | |


WA DEALER PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au



PLAN VIEW

(unit: mm)



TOP VIEW

