# **BACK BAR**



### \_\_\_ FEATURES / BENEFITS =\_\_

#### HOT GAS CONDENSATE SYTEM

Through SKIPIO's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

#### ■EFFICIENT REFRIGERATION SYSTEM

SKIPIO's refrigerators are designed with oversized and balanced refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### •FORCED AIR COOLING SYSTEM

Fast cooling and balanced temperature throughout the cabinet.

#### LED INTERIOR LIGHTING FOR ALL MODELS

Bright LED interior lighting is specifically designed for perfect visibility throughout the interior.

#### •MAGNETIC DOOR GASKETS

Magnetic door gastkers are of one piece construction, removable without tools for ease of cleaning and replacement.

#### HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure is foamed-in-place using high density, CFC CFC free polyurethane insulation.

#### ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE)

#### COATED WIRE SHELVES

#### ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

#### •FRONT BREATHING SYSTEM

Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.



Model	Doors	Capacity (Liters)	Shelves	Compressor (HP)	Amps (A)	Weight (Kg)	L X D X H (mm)
SB9-2G	2	165	4	1/4	2.5	70	900x550: 900mm

# **BACK BAR**

Model: SB9-2G

SPEC SHEET	SB9-2G		
Classification	Refrigerator		
Cabinet Dimension (WxDxH mm)	900x550x 900mm		
Capacity (Liters)	165		
Inner Temperature	1°C~8°C		
Doors	2		
Number of Shelves	4		
Refrigent	R-134a		
Compressor (Hp)	1/4		
Cooling Type	Fan cooling type		
Insulation Type	Polyurethane / Cyclopentane + CFC Free		
Temperature Control Type	Digital		
Amps (A)	2.5		
Voltage (V/Hz/Ph)	240V 50Hz 1Ph		
Power (W)	190		
Weight (Kg)	70		


#### WA DEALER PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au



# PLAN VIEW ,..

(unit: mm)



**TOP VIEW** 

