
Specifications Project RF6.UBF.1.SD Project ReFlex Series, 1 Solid Door Underbench Freezer Project Item No: Item No:



CABINET	
Door	1 × self-closing, lockable, reversible, solid swing door (hinged right hand)
Internal door opening	1 × door opening: 645 mm high × 485 mm wide
Shelves	3 × shelves: 2 × adjustable height and 1 × floor mounted
	Top and middle adjustable height shelves: 480mm wide × 350 mm deep
	Bottom floor mounted shelf: 480 mm wide × 180 mm deep
Worktop	n.a.
Material	304 AISI stainless steel interior and exterior
PERFORMANCE	
Max. ambient temperature	30°C
Temperature range	-21°C to -18°C (adjustable with SKOPE-connect™ -26°C to -12°C)
GEMS class	4L1
GEMS energy consumption	4.84 kWh/24 h
GEMS annual running cost	\$530 p.a. (@ \$0.30/kWh)
ELECTRICAL	
Electrical safety climate	4
class	
Interior lighting	n.a.
Power cord	Supplied with 1.6 m, 10 amp plug and lead
Power supply	220-240 volts a.c. 50 Hz, single phase supply
Current draw	1.5 amps
REFRIGERATION	•
Controller	SCS Connect (SKOPE-connect™ compatible)
Connectivity interface	Bluetooth wireless technology
Refrigeration system	Built-in, integral, freezer system
Refrigerant	R290/45 g (natural refrigerant)
Nominal capacity	250 watts
Heat rejection (avg/peak)	200 watts/205 watts
Drainage	No plumbing required

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2021 SKOPE Industries Limited

DIMENSIONS			
	External	Internal	
Height	850 mm	655 mm	
Width	600 mm	495 mm	
Depth	635 mm*	450 mm	
Floor area	0.38 m ²		
Weight	52 kg		
Gross volume	146 L		
Net volume	94 L		
* Depth 635 mm includes 35 mm rear stand-off			

Dimensional tolerances				
Before installing this cabinet allow the following dimensional				
tolerances:				
Linear dimensions	Overall cabinet dimensions			
Less than 1 metre	±5 mm			
More than 1 metre	-5 mm to +10 mm			
	Length of multiple cabinets			
	At each joint	At each end wall		
Less than 1 metre	±5 mm	+15 mm		
More than 1 metre	-5 mm to +10 mm	+15 mm		
More than 1 metre	-5 mm to +10 mm	+15 mm		

/entilation requirements		
Гор	Not required	
Sides	50 mm each side	
Back	35 mm (provided by rear stand-off)	
Bottom	30 mm (provided by feet)	

PSS0664 Rev. 1.4 Nov. 2022



WA DEALER PRACTICAL PRODUCTS PTY LTD PH: 08 9302 1299

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au