
specifications






RF6.UBR.1.SD

ReFlex Series, 1 Solid Door Underbench Fridge





850	820	600	SKOPE-connect™ compatible controller Coved internal floor —	600 35 Rear stand-	off Stainless steel — interior/exterior — Rear stand-off —Power cord
7	30	Floor clearance			
			Front levelling f	eet and rear rollers	Built-in integral refrigeration system (225 mm high × 220 mm deep)

CABINET				
Door	1 × self-closing, lockable, reversible, solid swing door (hinged right hand)			
Internal door opening	1 × door opening: 645 mm high × 485 mm wide			
Shelves	3 × shelves: 2 × adjustable height and 1 × floor mounted Top and middle adjustable height shelves: 480 mm wide × 350 mm deep Bottom floor mounted shelf: 480 mm wide × 180 mm deep			
Worktop	n.a.			
Material	304 AISI stainless steel interior and exterior			
PERFORMANCE				
Max. ambient temperature	30°C			
Temperature range	1°C to 4°C (adjustable with SKOPE-connect™ 1°C to 15°C)			
GEMS class	4M1			
GEMS energy consumption	1.30 kWh/24 h			
GEMS annual running cost	\$143 p.a. (@ \$0.30/kWh)			
ELECTRICAL				
Electrical safety climate class	4			

DIMENSIONS			
	External	Internal	
Height	850 mm	655 mm	
Width	600 mm	495 mm	
Depth	635 mm*	430 mm	
Floor area	0.38 m^2	•	
Weight	50 kg		
Gross volume	139 L		
Net volume	80 L		

Before installing this cabinet allow the following dimensional

-5 mm to +10 mm Length of multiple cabinets

-5 mm to +10 mm +15 mm

At each joint

Linear dimensions Overall cabinet dimensions

±5 mm

±5 mm

Dimensional tolerances

tolerances:

Less than 1 metre

More than 1 metre

Less than 1 metre

More than 1 metre

Current draw	1.0 amps		
REFRIGERATION			
Controller	SCS Connect (SKOPE-connect™ compatible)		
Connectivity interface	Bluetooth wireless technology		
Refrigeration system	Built-in, integral, refrigeration system		
Refrigerant	R600a/45 g (natural refrigerant)		
Nominal capacity	200 watts		
Heat rejection (avg/peak)	55 watts/60 watts		
Drainage	No plumbing required		

Supplied with 1.6 m, 10 amp plug and lead

220-240 volts a.c. 50 Hz, single phase supply

Ventilation requirements		
Тор	Not required	
Sides	50 mm each side	
Back	35 mm (provided by rear stand-off)	
Bottom	30 mm (provided by feet)	

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2021 SKOPE Industries Limited





At each end wall

+15 mm

Interior lighting

Power cord

Power supply

^{*} Depth 635 mm includes 35 mm rear stand-off