## specifications Refrigeration **TME650N-A Series** Project: ActiveCore Series, 1 Door (Glass), Upright Fridge Item No: 740 ĥ 745 PRACTICAL PRODUCTS 390 Double glazed 645 swing door 50 695\* Sign replacement Handle panel, or illuminated Power cord 335 Lit area 400 sign Sign SKOPE-connect<sup>™</sup> compatible controller LED interior lighting 2200 1720 80 Floor clearance 4 × 100mm high swivel castors (front lockable) (Ø70 wheel) CABINET Model ID TME650N-A TME650N-AC Doors 1 × self-closing, reversible, double glazed, single Low-E, lockable, argon filled, toughened safety glass swing door (hinged RH) Internal door opening 1 × door openings: 1570mm high × 620mm wide Shelves 5 × adjustable height wire shelves: 625mm wide × 470mm deep Sign Illuminated sign Sign replacement panel Material Powdercoat galvanized steel DIMENSIONS PERFORMANCE 40°C External Internal Max. ambient temp. 2200mm 1570mm Temperature range 1°C to 4°C (adjustable via SKOPE-connect 1°C to 15°C) Height Width 740mm 640mm **GEMS** class M1 M1 2.46 kWh/24h Depth 745mm 554mm GEMS energy consumption 2 36 kWh/24h 0.55m<sup>2</sup> GEMS annual running cost \$258 p.a.(@ \$0.30/kWh) Floor area \$269 p.a.(@ \$0.30/kWh) Weight 170ka ELECTRICAL Gross volume 610L Electrical safety climate class 5 \* Depth 695mm excludes removable door handle and door 1 × 1400mm, 15W LED 1 × 1400mm, 15W LED Interior side lighting lock bracket 1 × 670mm, 7W LED Sign lighting n.a. Dimensional tolerances Supplied with 2.3m, 10 Amp plug and lead Power cord Before installing this cabinet allow the following dimensional 220-240 Volts a.c. 50 Hz, single phase supply Power supply tolerances Current draw 2.9 Amps (includes unit 2.6 Amps) Linear dimensions Overall cabinet dimensions Less than 1 metre ±5mm REFRIGERATION -5mm to +10mm More than 1 metre SCS Connect (SKOPE-connect<sup>™</sup> compatible) Controller Length of multiple cabinets Connectivity interface Bluetooth At each end wall At each joint Top mounted, integral, removable ActiveCore refrigeration unit (UTHCNI-Less than 1 metre ±5mm +15mm Refrigeration system More than 1 metre -5mm to +10mm +15mm 0010) Refrigerant R290 / 99g (natural refrigerant) Ventilation requirements Nominal capacity 740 Watts 300mm Top 105 Watts/150 Watts Heat rejection (Avg/peak) Sides Not required Back Not required Drainage No plumbing required Bottom Not required

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2018 SKOPE Industries Limited



PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au

## PSS0517 Rev. 2.4 Jul. 2020

