







TOP MOUNT GLASS DOOR

MODEL: KR65-3G(HC) / KR65-3G-N

NATURAL Refrigerant



_= FEATURES / BENEFITS =__

■ Digital temperature control & monitor system

Keep rood products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ Hydrocarbon(HC) refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low affect to global warming (ODP-0, GWP-3).

■ Hot Gas Condensate System

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leaking from corrosion, but also prevents the overflow of condensate water.

■ Self Cleaning Condenser Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. When the dust accumulation is too much, their performance drops quickly resulting in possible spoiling of the contents. The self cleaning condenser keeps the condenser clean and prevents performance system failure by automatically brushing periodically.

■ Exterior & interior of the cabinet

The Turbo Air K-series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. The K-series adds a touch of style to the most refined setting.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

■ Meat Function

The Meat function allows the compressor to run continuously for up to 2 hours. When activated, the temperature drops quickly. This is ideal when you put new stock and need to chill/freeze it quickly. Also for aging meat and fish to an ideal temperature.

Adjustable, heavy duty, PE (polyethylene) coated wire shelves

Fridge holds 1°C ~ 8°C for the best in food preservation





LED interior lighting & fan control (only at Turbo Air)

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

■ Standard features

- · Anti-corrosion coated evaporator
- Self-contained system
- Standard 125mm. swivel castors with locks on the front set
- Door locks standard

Optional features

- 125mm castors fitted
- 180mm,105mm, 80mm castors optional
- Adjustable legs 100-155mm, 70-90mm



Best Value Commercial Refrigerator

TOP MOUNT GLASS DOOR

Fridge MODEL: KR65-3G(HC) / KR65-3G-N

Model KR65-3G-N(HC) Refrigerant R-290 COMP (HP) 1/4HP POWER INPUT(W) 450 Energy consumption 6.2 AMPS(A) 3/4.5 Capacity 1876 Product Dimension W 1900 Product Dimension D 850 Product Dimension H 1926 Weight 177 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Forced Evaporation Heater + Soaking Paperature		
COMP (HP) 1/4HP POWER INPUT(W) 450 Energy consumption 6.2 AMPS(A) 3/4.5 Capacity 1876 Product Dimension W 1900 Product Dimension D 850 Product Dimension H 1926 Weight 177 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Soaking Page	Model	KR65-3G-N(HC)
POWER INPUT(W) 450 Energy consumption 6.2 AMPS(A) 3/4.5 Capacity 1876 Product Dimension W 1900 Product Dimension D 850 Product Dimension H 1926 Weight 177 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Soaking Page	Refrigerant	R-290
Energy consumption AMPS(A) 3/4.5 Capacity 1876 Product Dimension W 1900 Product Dimension D 850 Product Dimension H 1926 Weight 177 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Soaking Page	COMP (HP)	1/4HP
AMPS(A) 3/4.5 Capacity 1876 Product Dimension W 1900 Product Dimension D 850 Product Dimension H 1926 Weight 177 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature Drainage / Heater + Soaking Page	POWER INPUT(W)	450
Capacity	Energy consumption	6.2
Product Dimension W Product Dimension D Product Dimension H 1926 Weight 177 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves 9 LED light Temperature range 1°C~8°C Ambient temperature Drainage / Heater + Soaking Page	AMPS(A)	3/4.5
Product Dimension D Product Dimension H Product Dimension H Weight T77 Stainless steel SUS 439 & SUS 430 SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range Ambient temperature Drainage / Heater + Soaking Page	Capacity	1876
Product Dimension H Weight Stainless steel Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range Ambient temperature Drainage / Heater + Soaking Page	Product Dimension W	1900
Weight 177 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Soaking Page	Product Dimension D	850
Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature Drainage / Heater + Soaking Page	Product Dimension H	1926
Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature Drainage / Heater + Soaking Page	Weight	177
Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature Drainage / Heater + Soaking Page	Stainless steel	SUS 439 & SUS 430
GN Pan Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Spaking Page	Features	
Door lock yes Adjustable Shelves 9 LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Spaking Page	Max GN Pan depth	
Adjustable Shelves LED light Temperature range Ambient temperature Drainage / Heater + Spaking Page	GN Pan	
LED light yes Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Spaking Page	Door lock	yes
Temperature range 1°C~8°C Ambient temperature 35°C Drainage / Heater + Spaking Page	Adjustable Shelves	9
Ambient temperature 35°C Drainage / Heater + Spaking Page	LED light	yes
Drainage / Heater + Soaking Page	Temperature range	1°C~8°C
Heater + Spaking Pane	Ambient temperature	35°C
roiceu Evaporation	Drainage / Forced Evaporation	Heater + Soaking Paper
Temperature control Digital control	Temperature control	Digital control
Cooling type FAN COOLING	Cooling type	FAN COOLING
Glass Type (Low-e / Heater / How many layer of the glass)	(Low-e / Heater /	Low-e /Heater


Design and specifications subject to change without notice.
Actual Shipping weight may differ due to extra packing materials for product protection.

- Door Locks Standard
- INTERIOR LED LIGHTING STANDARD
- SELF-CONTAINED SYSTEM
- STANDARD 3" SWIVEL CASTERS WITH LOCKS ON THE FRONT SET
- SOLID AND STURDY GRILLE DESIGN
- ALUMINIUM DOOR FRAME
- Low-E Double Glass










TOP VIEW



SIDE VIEW

AUSTRALIA BRANCH

WA DEALER PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au

