

ABXOLUT AX5-TS

MECHANICAL/CHEMICAL REPLACEMENT CARTRIDGE

Sediment, Rust, Dirt Particles reduction

Chlorine, Taste/ Odour reduction

Scale and Cloudiness reduction



WaterMark
AS 3497
Lic: 23066
**



AbXolut
ONE


Specification

Flow Rate: 7.5 L/min
Capacity: 25,000 litres
Micron Rate: 5
Ports (inlet/outlet): 15mm
Max. Temperature: 38°C
Min. Pressure: 172 kPa
Max. Pressure: 860 kPa (non-shock)

Dimension

80 mm (dia) x 300 mm (H)

Quick & easy to
replace the cartridge



Turn anti-clockwise
and pull downward



Push up and
turn clockwise
until stop

Filter Replacement Instructions

1. Shut off the water supply
2. Release the water pressure
3. Grasp existing filter and remove by rotating left until it stops, then pull down releasing it from the filter head
4. Align replacement filter guide channels with the corresponding posts of the filter head
5. Insert the filter upward until it fully seats into the head, then rotate right until it stops
6. Flush the system for 5 minutes before use

WA DEALER
PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299
51 Paramount Dr Wangara WA 6065
sales@practicalproducts.com.au
www.practicalproducts.com.au