

BLIXER 3D | INSTRUCTIONS

About -

- Requires 10 AMP power supply (draws 6 AMP)
- Place unit on a stable surface



WARNING: Always take care when handling the blade (they are very sharp!)

Assembly -

- 1) Face motor unit towards you, and place bowl over shaft with handle slightly to the left.
- 2) Turn bowl handle to the right until bowl is positioned correctly with handle straight in front of you.
- 3) Position blade onto the shaft and lower until completely at the bottom of bowl.
- **4)** Ensure scraper arm is correctly assembled with lid and handle.
- 5) Place lid on bowl and rotate to the right until it clicks in place. It is now ready for use!

Control Panel & Usage -

RED Button	STOP
GREEN Button	ON
BLACK Button	PULSE MODE

To Use -

- This machine texturally modifies product very quickly, therefore it is recommended you keep a close eye on the mixture in order to obtain desired results
- Maximum bowl fill is 2 Kgs
- Never run machine for extended periods of time. It is designed to operate in short bursts
- ❖ Machine is fitted with an Overtemp located underneath the motor unit. This automatically stops the motor is it has been overloaded



NOTE:

Should overloading happen, allow machine to cool down before resetting Overtemp and modify use

Cleaning -

- Always unplug power
- Machine components can be washed with detergent and dried for future use
- Not suitable for dishwashers and do not use abrasives for cleaning
- Never immerse the motor unit in water, wipe with damp cloth only

